

**SCOPE:** This specification applies to – CCFXX0V5 - Plug




**SPECIFICATIONS:**

Number of poles: 2 – 20  
 Sides configuration: Flanges  
 Pitch: 5.08 mm  
 Voltage: 300V  
 Current: 12A  
 Wire section: 0.05 - 2.5 mm<sup>2</sup> / 30 – 12 AWG  
 Available approvals: UL, IEC


Insertion force per pole: 3 N  
 Withdrawal force per pole: 1,5 N  
 Stripping length: 10 mm  
 Operating temperature range: - 40°C to +105°C  
 Contact resistance: <15 mOhm  
 Insulation resistance: >1 GOhm

Terminal contact: Tin plated copper alloy  
 Spring tightening: Stainless steel  
 Insulating housing material: PA polyamide  
 Color: Green (Standard)  
 Spring tightening: Stainless steel

**DIMENSIONS:**



**Mates with:**  
 CIM series  
 CIMH series  
 CPM series



<p><b>BlockMaster</b>                  Confidential and                  Proprietary</p>	<p><b>BlockMaster Electronics</b>                  1400 Howard Street                  Elk Grove Village, IL. 60007                  Toll Free: 800-595-8881 FAX: 847-956-1690  <a href="http://www.blockmaster.com">www.blockmaster.com</a></p>
<p>All dimensions are in MM unless otherwise specified</p>	
<p>Drawing Number:                  CCFXX0V5</p>	<p><b>Plug</b></p>
<p>Date:                  6/11/2017</p>	<p>THE INFORMATION DISCLOSED HEREIN WAS ORIGINATED BY AND IS THE PROPERTY OF BLOCKMASTER ELECTRONICS INC. AND EXCEPT FOR USE EXPRESSLY GRANTED TO THE UNITED STATES GOVERNMENT BLOCKMASTER ELECTRONICS INC. RESERVES ALL PATENT PROPRIETARY DESIGN, USE, SALE, MANUFACTURING AND PRODUCTION RIGHTS THERETO. THIS DOES NOT APPLY TO VENDOR.</p>